




Plastic Modular Belt

Series **uni CNB** Type **18% Open**



Straight running belt
Nominal pitch: 25.4 mm (1.00 in)
Surface type: Flat
Surface opening: 18%
Backflex radius: 40.0 mm (1.60 in)
Pin diameter: 5.0 mm (0.20 in)

Belt material & color	PP W		mm	in		mm	in
		P (Nominal)	25.4	1.00	T	8.8	0.35
Pin material & color	 PP W	R	3.0	0.12	L	4.4	0.17

Non standard material and color: See uni Material and Color Overview.

Belt width		Permissible tensile force (Belt/pin material)		Belt weight (Belt/pin material)		*Min. No. drive sprocket per shaft	Number of wear strips (Min. No.)	
		PP/PP		PP/PP			**Carry (pcs)	**Return (pcs)
mm	in	N	lbf	kg/m	lb/ft			
77	3.0	539	121	0.3	0.18	2	2	2
153	6.0	1071	241	0.5	0.36	2	2	2
229	9.0	1603	360	0.8	0.54	2	2	2
305	12.0	2135	480	1.1	0.72	3	3	2
381	15.0	2667	600	1.3	0.90	3	3	2
457	18.0	3199	719	1.6	1.07	4	4	2
533	21.0	3731	839	1.9	1.25	4	4	2
609	24.0	4263	958	2.1	1.43	5	5	3
685	27.0	4795	1078	2.4	1.61	5	5	3
761	30.0	5327	1197	2.7	1.79	6	6	3
837	33.0	5859	1317	2.9	1.97	6	6	3
913	35.9	6391	1437	3.2	2.15	7	7	4
989	38.9	6923	1556	3.5	2.33	7	7	4

Additional standard belt widths are available in steps of 76.0 mm (2.99 in). Additional non-standard belt widths are available in steps of 12.7 mm (0.50 in).

1977	77.8	13839	3111	6.9	4.65	14	14	7
------	------	-------	------	-----	------	----	----	---

Additional standard belt widths are available in steps of 76.0 mm (2.99 in). Additional non-standard belt widths are available in steps of 12.7 mm (0.50 in).

2965	116.7	20755	4666	10.4	6.97	20	20	10
------	-------	-------	------	------	------	----	----	----

General belt tolerance is +0/-0.4% at 23°C/73°F and 50% RH. For exact belt width contact Customer Service. Non standard belt width on request.


*Max. Load per Drive Sprocket. Belt material: PP 500 N (112 lbf)

**Max. Spacing between wear strips, Carry: 152.0 mm (6.00 in); Return: 304.0 mm (12.00 in)

= Single Link

Accessories

Flight




Type	Material & color	H		Link size	Width		Indent	
		mm	in		mm	in	mm	in
22% Flat	PE  PP-I 	5.0	0.20	K300	75.9	2.99	6.4	0.25
				K600	152.0	5.98		
Flat/waves*	POM-D  PE 	25.4	1.00	K600	152.0	5.98	0.0	0.00
	PP-I  PP-I 	50.8	2.00					
		76.2	3.00					

Minimum bricklaid indent is 38.1 mm (1.50 in). Increment: 12.7 mm (0.50 in).
*Flat/waves also available with 26.0 mm (1.02 in) molded indent.
Non Standard material and color: See uni Material and Color Overview.

Accessories

Side Guard



Type	Material & color	H		A (Min.)		B (Min.)		C (Min.)		D (Min.)	
		mm	in	mm	in	mm	in	mm	in	mm	in
Closed	PP-I  	25.4	1.00	12.5	0.49	18.5	0.73	25.5	1.00	31.5	1.24
		50.8	2.00								
		76.2	3.00								

Minimum indent to outside of Side Guard: 14.0 mm (0.55 in). Increment 6.4 mm (0.25).
Non Standard material and color: See uni Material and Color Overview.
Backflex radius for Side Guard: 75.0 mm (2.95 in)


Sprocket

No of teeth	Bore size								Overall diameter		Pitch-diameter		Hub-diameter		A-dimension		B-dimension		Double row/Two way	PA6 LG	
	Pilot bore	in	0.98	1.00	1.18	1.25	1.50	1.57												Molded	LG
		mm	25.0	25.4	30.0	31.8	38.1	40.0	mm	in	mm	in	mm	in	mm	in					
Z10	✔		●	●	●	●			80.0	3.15	82.2	3.24	70.0	2.76	34.7	1.37	45.5	1379	✔	✔	
Z12	✔			●	●	●			96.8	3.81	98.1	3.86	70.0	2.76	43.0	1.69	53.5	2.11	✔	✔	
Z15	✔			●	●	●			121.5	4.78	122.2	4.81	70.0	2.76	55.3	2.18	65.5	2.58	✔	✔	
Z18	✔				●	●	●	●	146.0	5.75	146.3	5.76	70.0	2.76	67.6	2.66	77.5	3.05	✔	✔	
Z19	✔				●	●	●	●	154.2	6.07	154.3	6.07	70.0	2.76	71.7	2.82	81.6	3.21	✔	✔	

Molded sprocket



Molded sprocket



Other sprocket sizes are available upon request.
 Two-part sprockets are available upon request..
 Other bore sizes are available upon request.
 uni Retainer Rings: See uni Retainer Ring data sheet.
 Width of tooth = 12.0 mm (0.47 in)
 Width of sprocket = 25.0 mm (0.98 in)

Max load per sprocket shown does not take bore size into account.
 Please also ensure that sufficient size shaft is chosen for corresponding load.

For correct sprocket position: See uni Assembly Instructions for uni CNB.
 For more detailed sprocket information, contact Customer Service.

Non standard material
 and color: See uni Material
 and Color Overview.

uni CNB 18% Open/2023.08.24



Synthetic Belts



Endless Woven Belts



Modular Belts



Engineered Belts



Homogeneous Belts



Fabrication & Service

**Expert advice and quality solutions
 for all your belting needs.**

ammeraalbeltech.com
 eptool.online

Ammeraal Beltech Modular A/S
 Hjulmagervej 21
 DK-7100 Vejle
 T +45 7572 3100

ammega.com

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.

Member of Ammega Group.